## The micromechanics of fault gouge and dynamic earthquake triggering: investigation by Discrete Element Method numerical simulations

Michele Griffa<sup>1</sup>, Eric G. Daub<sup>2,3</sup>, Robert A. Guyer<sup>2,4</sup>, Paul A. Johnson<sup>2</sup>, Chris Marone<sup>5,6</sup>, and Jan Carmeliet<sup>1,7</sup>







Laboratory for Building Science and Technology, EMPA
 Geophysics Group, Los Alamos National Laboratory
 Center for Nonlinear Studies, Los Alamos National Laboratory
 Department of Geosciences Department State University

5. Department of Geosciences, Pennsylvania State University
6. G3 Center and Energy Institute, Pennsylvania State University
7. Department of Architecture, ETH Zurich








Supported by institutional LDRD funding (LANL) and Swiss National Science Foundation (EMPA)

## DYNAMIC EARTHQUAKE TRIGGERING Peak velocity 4 cm s<sup>-1</sup> 0 2 cm s<sup>-1</sup> 0 1 cm s<sup>-1</sup> 0

Experiments (Johnson et al., 2008)

Seismic waves can trigger unstable fault slip.

Goal: explore mechanics of a sheared granular material subjected to external vibration to simulate passing seismic waves



## When vibration is applied, stick-slip event occurs earlier = dynamic triggering. Look at microscopic deformation to better understand effect of vibration 0.9 No applied vibration Applied vibration 0.85 0.85 (a) (b) (c) (1) (3) (4) (5) (6) (6)

0.65


## NON-AFFINE DEFORMATION

1600

Time (ms)

1900


How does vibration affect particle scale deformation? Need a metric to quantify inelastic deformation



For each particle, find best fitting strain tensor to map neighboring particles to their new positions = "affine" or elastic deformation.

Deviations from this are inelastic = "non-affine," quantified by metric M (sum of residuals over all particles in neighborhood)

(Falk and Langer, 1998)



mation in the granular layer.

